

Picture	Name	Description/Technical data			
	<b>Sensor cable 3 m, 15 kOhm, Santoprene</b>	Wire sensor 2x0,75 mm <sup>2</sup> , NTC 15 kOhm at 25 °C, Ø5 mm, black Santoprene (TPV) outer sheath, IP 67, Temp. range -25 °C to 90 °C	Temp., °C	Resistans, kOhm	Art. no. 140F1091 EAN no. 5703466209301
	<b>Temperature Sensor 10 m NTC 15k Santoprene</b>		-10	66,1	Art. no. 140F1098 EAN no. 5703466210734
			-5	52,5	
			0	41,1	
			5	33,2	
			10	27,0	
			15	22,1	
			20	18,2	
			25	15,0	
			<b>Temperature Sensor 40 m NTC15k Santoprene</b>	30	
35	10,4				
40	8,7				
45	7,4				
50	6,2				
	<b>Outdoor sensor 2,5 m, 15 kOhm, PVC, DIN 44574</b>	Wire sensor, 2x0,75 mm <sup>2</sup> , NTC 15 kOhm at 25 °C, Ø10 mm, white PVC outer sheath, IP 67, Temp. range -25 °C to 70 °C			Art. no. 140F1092 EAN no. 5703466209318
	<b>Silicon temperature sensor for DEVlreg™ 330 (60-160°C), NTC 16,1 kOhm @ 100°C</b>	Wire sensor, 2,5 m, 2x0,75 mm <sup>2</sup> , NTC 16,1 kOhm at 100 °C, Ø9 mm, IP 65, Temp. range 50 °C to 170 °C			Art. no. 140F1097 EAN no. 5703466209707
	<b>Flexpipe Ø6,7 mm, 2,5 m</b>	Package 170 x 240 x 20 mm, inner Ø6,7 mm, outer Ø10 mm, Black			Art. no. 140F1114 EAN no. 5703466215234
	<b>AstroFlex FFYTL Ø8,5 mm, roll 50 m</b>	Package 400 x 130 x 400 mm, Flexpipe for sensor and cable protection.			Art. no. 19809100 EAN no. 5703435009314
	<b>Sensor shell M20</b>	Size 95 x Ø20 mm inner Ø10,5 mm, inner Ø19,9 mm			Art. no. 12500112 EAN no. 5703435031025
	<b>Sensor end-cap brass for Flexpipe Ø6,7 mm</b>	Package 60 x Ø12 mm, size 60 x Ø12 mm, inner Ø6,7 mm, inner Ø10 mm			Art. no. 12500120 EAN no. 5703466111543
	<b>Accessory kit Elements Transition Pipe</b>	Mounting kit for 3 m wire sensor			Art. no. 18055354 EAN no. 5703466124420