CU-Band, verzinnt, 250A, 6x16x0,8mm, schwarz

Typ CU-BAND6X16X0,8-BK
Art.-Nr. 081310
Katalog Nr.

Lieferprogramm

Sortiment			Allgemeines Schaltschrankzubehör
Zubehör			Kupferband isoliert
Zubehör			Kupferband isoliert
Beschreibung			Lamellierter Leiter E-Cu, verzinnt UL-approbiert bis max. 600 V AC Isoliermaterial wärmebeständig bis +105 °C
Bemessungsspannung	U_e	V AC	1000
Bemessungsspannung	U_e	V DC	1500
Durchschlagfestigkeit		kV/ mm	20
Selbstverlöschend			nach UL 94 V0
Länge		mm	2000
Bemessungsbetriebsstrom	I_e	A	250
Abmessungen (B x H x T)		mm	6 x 16 x 0.8
Querschnitt		mm^2	74.4
Cu-Zahl		kg	1,43
Farbe			Schwarz, ähnlich RAL 9005

Hinweise

[1)]Bemessungsbetriebsstrom: in Anlehnung an VDE 0281

[2)]Querschnitt: Verdrahtungshinweise bei Geräten (z. B. Anschlussquerschnitt mindestens … mm^2) sind vorrangig zu beachten

[3)]Cu-Zahl: Berechnung Materialzuschlag → Kapitel Allgemeines

Approbationen

Product Standards	UL 758; EN 60439-1, -3; CE marking
UL File No.	E248096
UL Category Control No.	AVLV2
CSA File No.	UL report applies to both US and Canada
CSA Class No.	–
North America Certification	UL listed, certified by UL for use in Canada
Conditions of Acceptability	max. 105 °C
Specially designed for North America	No
Suitable for	Appliance Wiring Material - Component
Max. Voltage Rating	600 V AC, 750 V DC

© 07/2014 by Eaton Industries GmbH