









## Leiteranschlussklemme, 16-70qmm, 10 mm

Typ **AKU70/10**  
Art.-Nr. **107193**

Katalog Nr.

### Lieferprogramm

Sortiment			60-mm-System 185-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	14 x 14
Breite		mm	20.5
Bemessungsbetriebsstrom	$I_e$	A	400
Cu-Schiene		mm	16 - 70 mm <sup>2</sup> AWG 4 - AWG 2/0.  direkt geklemmt,   2 x (3 x 9 x 0.8) oder 6 x 9 x 0.8
verwendbar für			Alle 10 mm dicken Flachschielen
<b>Hinweise</b>			
○ Rundleiter eindrätig			
 Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse			
⊙ Rundleiter mehrdrätig			
⊖ Sektorleiter eindrätig			
⊖ Sektorleiter mehrdrätig			
 CU-Band			
 CU-Schiene			

### Approbationen

Product Standards  
UL File No.  
UL Category Control No.  
CSA File No.  
CSA Class No.  
North America Certification  
Conditions of Acceptability  
Specially designed for North America  
Suitable for  
Current Limiting Circuit-Breaker  
Max. Voltage Rating  
Degree of Protection

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking  
E307559  
NMTR2, NMTR8  
236217  
3211-37  
UL recognized, CSA certified  
Refer to approbation report  
No  
Feeder circuits  
Refer to approbation report  
600 V AC  
Feeder circuits

### Abmessungen

