



## Main

Range of product	Easy UPS 1Ph On-Line
Product or component type	Uninterruptible power supply (UPS)
Provided equipment	Mounting bracket USB cable Power cord User manual Software CD
Mounting support	Mounting accessory
Communication port protocol	RS232 SmartSlot USB
Reset	Automatic reset
Function available	Internal bypass Optional communication kit for remote monitoring With LCD display Energy efficiency Intelligent charging algorithm monitors battery and AC supply
Topology	Double conversion online

## Complementary

Display type	LCD display
Integrated connection type	USB port
Surge Energy	600 J
Type of signal	Sine wave
Input voltage	230 V AC nominal mode
Output voltage	220 V on nominal mode 230 V on nominal mode 240 V on nominal mode
Protection type	Surge arrester Circuit breaker
Network frequency	40...70 Hz
Output frequency	50...60 Hz
Power range	3000 VA
Electrical connection	1 outlet (output) IEC 320 C19 6 outlet (output) IEC 320 C13 1 inlet (input) IEC 320 C20

Local signalling	Alarm distinctive (low battery) Alarm continuous or intermittent tone (overload) LCD display (status and alert)
Number of cables	1
Battery type	Internal battery Lead-acid battery Sealed rechargeable
Number of batteries	6
Charging time	4 h recover to 90% capacity
Battery capacity	9 Ah
Product weight	27.6 kg
Height	86 mm
Width	437 mm
Depth	632 mm

## Environment

Acoustic level	< 50 dBA
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Storage altitude	0...15000 m
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Product certifications	CE

## Contractual warranty

Warranty period	2 years
-----------------	---------