Product data sheet Characteristics

XBP48RM1U-LI APC Smart-UPS 48V 585 Wh LI Battery Pack

has not been replaced. Please contact your customer care center for more information.



	rv	

Model Name	APC Smart-UPS 48V 585 Wh LI Battery Pack
Includes	4 post rail kit , Comms cable , Grounding Cable , Installation guide , Rack Mounting brackets
Standard Lead Time	Usually in Stock
Product Distribution	Australia , Austria , Belgium , Croatia , Czech Republic , Denmark , Finland , France , Germany , Greece , Hong Kong , Hungary , Iceland , Ireland , Israel , Italy , Netherlands , New Zealand , Norway , Poland , Portugal , Russian Federation , Singapore , Slovakia (Slovak Republic) , Spain , Sweden , Switzerland

Output

Battery Output Voltage	48
Dallely Outbut vollage	40

Batteries & Runtime

Battery Volt-Amp-Hour Capacity	585
Battery Type	Lithium Ion
Battery mounting	Rack Mount
Battery mounting	5 - 10

Physical

Model Name	APC Smart-UPS 48V 585 Wh LI Battery Pack	
Includes	4 post rail kit , Comms cable , Grounding Cable , Installation guide , Rack Mounting brackets	
Standard Lead Time	Usually in Stock	
Product Distribution	Australia , Austria , Belgium , Croatia , Czech Republic , Denmark , Finland , France , Germany , Greece , Hong Kong , Hungary , Iceland , Ireland , Israel , Italy , Netherlands , New Zealand , Norway , Poland , Portugal , Russian Federation , Singapore , Slovakia (Slovak Republic) , Spain , Sweden , Switzerland	
Output		
Battery Output Voltage	48	
Batteries & Runtime		
Battery Volt-Amp-Hour Capacity	585	
Battery Type	Lithium Ion	
Battery mounting	Rack Mount	
Battery mounting	5 - 10	
Net Weight	13.02 kg	
Net Weight Maximum Height	43.0 mm	
Net Weight Maximum Height Maximum Width	43.0 mm 432.0 mm	
Net Weight Maximum Height Maximum Width Maximum Depth	43.0 mm 432.0 mm 521.0 mm	
Net Weight Maximum Height Maximum Width Maximum Depth Shipping Weight	43.0 mm 432.0 mm 521.0 mm 18.64 kg	
Net Weight Maximum Height Maximum Width Maximum Depth Shipping Weight Shipping Width	43.0 mm 432.0 mm 521.0 mm 18.64 kg 600.0 mm	
Net Weight Maximum Height Maximum Width Maximum Depth Shipping Weight Shipping Width Shipping Height	43.0 mm 432.0 mm 521.0 mm 18.64 kg 600.0 mm 200.0 mm	
Net Weight Maximum Height Maximum Width Maximum Depth Shipping Weight Shipping Width Shipping Height Shipping Depth	43.0 mm 432.0 mm 521.0 mm 18.64 kg 600.0 mm	
Physical Net Weight Maximum Height Maximum Width Maximum Depth Shipping Weight Shipping Width Shipping Height Shipping Depth Rack Height Color	43.0 mm 432.0 mm 521.0 mm 18.64 kg 600.0 mm 200.0 mm	

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000 meters

Conformance

Approvals	UL 1973
Standard warranty	5 year repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant