

Part no. F3A-2K-D70/3
EP-501499

General specifications		
Product name		Eaton xEnergy Basic LV systems Low voltage switchgear
Part no.		F3A-2K-D70/3
EAN		9010653053187
Product Length/Depth		140 millimetre
Product height		17.5 millimetre
Product width		230 millimetre
Product weight		0.2 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		LV systems
Product Sub Type		Low voltage switchgear
Delivery program		
Type		Accessory xEnergy series Accessory CS Accessory exterior fitting
Model		Membrane
Accessory/spare part type		Flanges
Technical Data - Mechanical		
Shape		Straight
Surface finishing		RAL 7035, light gray RAL 7001, silver gray
Surface protection		Untreated
Material		Plastic
Degree of protection		IP55 Other
Number of connector holes		12
Thickness		4 mm
Thread type		None
Suitable for nominal thread (PG) - min		3
Suitable for nominal thread (PG) - max		70
Additional information		
Features		Pre-stamping
Special features		Membrane flange (push-through cable entry), RAL 7035 / RAL 7001, compound of polyamide (PA) and thermoplastic elastomer (TPE)
Used with		Accessory CS Accessory exterior fitting

Technical data ETIM 8.0

Elektroverteiler-Systeme (inkl. Installationsverteiler) (EG000023) / Einführungsflansch für Kleingehäuse/Schaltschrank (EC000211)		
Elektro-, Automatisierungs- und Prozessleittechnik / Elektroinstallationsanlage, -gerät / Elektroverteiler-System (inkl. Installationsverteiler) / Einführungsflansch für Kleingehäuse/Schaltschrank (ec1@ss10.0.1-27-14-24-21 [ADI315007])		
Model		Membrane
Type		Straight
Width	mm	230
Height	mm	17.5
Depth	mm	140
Material		Plastic
Surface protection		Untreated
Degree of protection (NEMA)		Other
Pre-stamping		Yes

Number of connector holes			12
Thread type			None
Suitable for nominal thread metric/PG			3 - 70